

MPH SERIES

Low Profile Hex Link Hydraulic Torque Wrench

- Working pressure 10000 psi max; accuracy $\pm 3\%$
- 360° adjustable swivel assembly
- Compact design with longer reaction pad for improved durability
- Compact design using composite materials to give improved strength
- The new locking coupler ensures oil always flows to the wrench head



MPH series

Type	Torque (ft.lbs)		Ratchet Link (inch)	Drive Cylinder (lbs)	Cassettes (lbs)	Dimension (inch)					A (inch)	R (inch)
	Min	Max				L	H1	H2	W1	W2		
2MPH	170	~ 1,696	7/8" ~ 2-3/16"	2.20	3.52	7.69	4.96	4.03	1.26	2.01	0.39~0.63	1.06~1.69
	177	~ 1,770	2-3/8"	2.20	3.74	7.69	5.06	4.14	1.26	2.016	0.43	1.81
4MPH	431	~ 4,314	1-1/4" ~ 2-9/16"	4.40	9.68	10.15	97	5.35	1.65	2.607	0.55~0.63	1.42~2.09
	476	~ 4,775	2-3/4" ~ 3-1/8"	4.40	10.12	10.35	37	5.74	1.65	2.60	0.59	2.2~2.4
8MPH	808	~ 8068	1-7/16" ~ 3-11/16"	7.26	17.60	11.96	8.16	6.66	2.09	3.27	0.63~0.87	1.81~2.36
	867	~ 8864	3-7/8" ~ 4-1/4"	7.26	18.48	11.96	8.51	7.01	2.09	3.27	0.67	2.95~3.07
14MPH	1,364	~ 13,644	2" ~ 4-5/8"	12.10	25.52	14.25	9.42	8.04	2.52	3.09	0.75~1.22	2.36~3.43
	3,083	~ 30,828	2-3/8" ~ 6-1/8"	25.08	63.80	16.57	11.94	10.72	3.35	5.16	0.98~1.14	3.03~4.53
30MPH	3,282	~ 32,819	6-1/2" ~ 6-7/8"	25.08	66.00	17.05	12.41	11.23	3.35	5.16	1.06~1.42	4.8~5.04

