



MSD SERIES

Square Drive Hydraulic Torque Wrench

by MID Industrial Tools

- Working pressure 10,000 psi max
- Constantly repeatable accuracy $\pm 3\%$
- 360° adjustable swivel assembly
- Easily replaceable square and hexagon drive adapters
- Suitable for continuous operation at maximum pressure
- Heavy-duty aluminum-titanium composite, lightweight body
- 360° adjustable reaction arm with safety lock



MSD Series Specifications

Model	Square Drive	Torque (ft-lbs)		Weight (lbs)	Dimensions (inches)							
		Min	Max		L1	L2	H1	H2	H3	H4	R1	R2
07 MSD	3/4"	81	814	3	4.37	5.47	1.65	2.60	2.99	4.25	0.83	2.68
1 MSD	3/4"	135	1,354	6	5.71	6.85	1.97	2.83	3.78	5.16	1.02	3.35
3 MSD	1"	332	3,325	11	7.01	9.02	2.68	3.74	5.00	6.97	1.34	4.49
5 MSD	1-1/2"	554	5,548	18	8.31	10.67	3.15	4.84	5.87	7.83	1.54	5.93
8 MSD	1-1/2"	794	7,945	24	8.74	11.54	3.54	5.28	6.57	8.54	1.85	6.02
10 MSD	1-1/2"	1,143	11,435	33	9.69	12.52	3.94	5.59	7.17	9.13	2.01	6.06
20 MSD	2-1/2"	1,965	19,651	62	12.13	15.12	4.72	7.20	8.66	10.63	2.32	7.32
25 MSD	2-1/2"	2,559	25,592	77	12.72	15.79	5.39	7.87	9.72	11.69	2.60	7.83
35 MSD	2-1/2"	3,586	35,867	104	14.69	18.33	6.02	8.50	11.10	13.07	3.03	9.49
50 MSD	2-1/2"	5,306	53,064	192	15.75	20.31	6.30	8.78	11.46	13.43	3.19	10.20

Specifications subject to change without notice.

